

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** V-TAC

**Supplier's address:** V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

**Model identifier:** 138

## Type of light source:

|   |     |                                 |     |
|---|-----|---------------------------------|-----|
| Lighting technology used:                           | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | E14 |                                 |     |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No  | Envelope:                       | -   |
| High luminance light source:                        | No  |                                 |     |
| Anti-glare shield:                                  | No  | Dimmable:                       | No  |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|  |                         |  |                                    |
|--|-------------------------|--|------------------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 6                       | Energy efficiency class  | F                                  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 470 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                              |
| On-mode power ( $P_{on}$ ), expressed in W   | 6,0                     | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                               |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                                 |
| Outer dimensions without   | Height                  | 86   | Spectral power distribution in the |
|  | Width                   | 50   |                                    |
|  | Depth                   | 50   |                                    |
|  |                         |  | See image in last page             |

|   |                   |  |                                      |  |
|---|-------------------|--|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |                   |  | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>  | Yes               | If yes, equivalent power (W)                                       | 40                                   |  |
|   |                   | Chromaticity coordinates (x and y)                                 | 0,450<br>0,410                       |  |
| <b>Parameters for directional light sources:</b>  |                   |  |                                      |  |
| Peak luminous intensity (cd)  | 150               | Beam angle in degrees, or the range of beam angles that can be set | 120                                  |  |
| <b>Parameters for LED and OLED light sources:</b>   |                   |  |                                      |  |
| R9 colour rendering index value   | 6                 | Survival factor  | 1,00                                 |  |
| the lumen maintenance factor  | 0,96              |  |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |                   |  |                                      |  |
| displacement factor (cos $\phi_1$ )   | 0,56              | Colour consistency in McAdam ellipses                              | 3                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | .. <sup>(b)</sup> | If yes then replacement claim (W)                                  | -                                    |  |
| Flicker metric (Pst LM)   | 1,0               | Stroboscopic effect metric (SVM)                                   | 0,9                                  |  |

(a) : not applicable;

(b) : not applicable;

